



KEY FEATURES

- Safe Crimp System (SCS) control
- Large production capacity (small/medium bore)
- Low noise level
- Precise
- Robust
- Available with SCE control panel

STANDARD



TECHNICAL SPECIFICATIONS

<b>CAPACITY*</b>	<b>NOISE LEVEL</b>
2wb: 1¼" max.	<69 dB A
4ws: 1¼" max.	<b>MOTOR</b>
<b>CRIMP RANGE</b>	4 Kw
4 - 70 mm (0.157 - 2.756")	<b>VOLTAGES</b>
<b>CRIMP FORCE</b>	220/240 V, 3Ph, 50 Hz
140 t	380/415 V, 3Ph, 50 Hz
<b>OPENING WITH DIES</b>	208/240 V, 3Ph, 60 Hz
+45 mm (+1.772")	<b>DIMENSIONS</b>
<b>COMPLETE OPENING</b>	845 x 790 x 1400 mm
125 mm (4.921")	(33 x 31 x 55")
<b>MASTER DIE LENGTH</b>	<b>PACKAGING</b>
80 mm (3.150")	1120 x 1020 x 1770 mm
<b>STANDARD DIES</b>	(44 x 40 x 70")
15, 18, 21, 24, 27, 30, 33, 36, 39, 42, 45, 48	<b>NET WEIGHT</b>
	600 kg

OPTIONAL



\*Indicative capacities depending on hose and fitting type