

P CRIMP 140

ASSEMBLING FOR MASS PRODUCTION
STAND TYPE CRIMP MACHINE, SCS SYSTEM



KEY FEATURES

- Safe Crimp System (SCS) control
- Large production capacity (small/medium bore)
- Low noise level
- Precise
- Robust
- Available with SCE control panel

STANDARD



TECHNICAL SPECIFICATIONS

CAPACITY*	NOISE LEVEL
2WB: 2" max.	<69 dB A
4WS: 1 1/4" max.	MOTOR
Industrial: 2-1/2" max.	5.5 kW
CRIMP RANGE	VOLTAGES
4 - 70 mm (0.157 - 2.756")	220/240 V, 3Ph, 50 Hz
CRIMP FORCE	380/415 V, 3Ph, 50 Hz
140 t	208/240 V, 3Ph, 60 Hz
OPENING WITH DIES	DIMENSIONS
+45 mm (+1.772")	890 x 690 x 1380 mm
COMPLETE OPENING	(35 x 27 x 54")
125 mm (4.921")	PACKAGING
MASTER DIE LENGTH	1120 x 1020 x 1725 mm
80 mm (3.150")	(44 x 40 x 68")
STANDARD DIES	NET WEIGHT
14, 16, 18, 20, 22, 24, 27, 30, 33, 36, 39, 42, 45, 48	600 kg (1323 lb)

*Indicative capacities depending on hose and fitting type

OPTIONAL

