

P CRIMP 320

ASSEMBLING FOR MASS PRODUCTION
STAND TYPE CRIMP MACHINE

KEY FEATURES

- High crimp force
- Large opening
- Safe Crimp System (SCS) control
- Wide family of dies for industrial hoses
- Robust structure
- Fast and ergonomic
- Low noise level

STANDARD



Quick Change Gun

SCS Safe Crimp System

Mirror

Electrical Footswitch

Die Storage

Pushing panel

TECHNICAL SPECIFICATIONS

CAPACITY*

2wb: 3" max.

4ws: 2" max.

6ws: 2" max.

Industrial: 4" max.

NOISE LEVEL

<65 dB A

MOTOR

5.5 kW / 7.5 kW (Fast Version)

VOLTAGES

220/240 V, 3Ph, 50 Hz

380/415 V, 3Ph, 50 Hz

208/240 V, 3Ph, 60 Hz

380/415 V, 3Ph, 60 Hz

CRIMP RANGE

4 - 130 mm (0.157 - 5.118")

CRIMP FORCE

320 t

OPENING WITH DIES

+80 mm (+3.149")

COMPLETE OPENING

207 mm (8.149")

MASTER DIE LENGTH

100 mm (3.937")

STANDARD DIES

14, 16, 18, 20, 22, 24, 27, 30,
33, 36, 39, 42, 45, 48, 54, 57,
63, 66, 70, 73, 76

DIMENSIONS

1240 x 995 x 1615 mm

(49 x 39 x 64")

PACKAGING

1400 x 1100 x 1960 mm

(55 x 43 x 77")

NET WEIGHT

2000 kg (4409 lb)

GROSS WEIGHT

2300 kg (5071 lb)

*Indicative capacities depending on hose and fitting type

OPTIONAL



Die Storage Panel

Marking Dies

Back View Camera

Aluminium Quick Change Gun

Mechanical Backstop

Side Table

Die Sets for Brake & Air Conditioning Hoses

Digital Caliper

Barcode Reader