# HOSE ASSEMBLY MACHINES

### **S CUT 55/P**

### FULL SERVICE WORKSHOP, STARTER PRODUCTION UNITS STAND TYPE CUTTING MACHINE



#### **KEY FEATURES**

Versatile, slotted blade for high performance with minimal smoke

Ergonomic and functional design

Double foot pedal system

Safety cover and feeding guides for hose (easy and fast cutting operation)

Digital counter for maintenance assistance

Adjustable speed for cutting on pneumatic version







Control Panel

Slotted Blade

Feeding Guide

**TECHNICAL SPECIFICATIONS** 

## CAPACITY 2wb: 2" max.

4ws: 2" max.

6ws: 2" max.

Industrial: 2"

#### **ROTATION SPEED**

3000 rpm

#### SLOTTED BLADE DIAMETER

400 mm (15.7")

#### MAX HOSE OD.

80 mm (3.15")

#### MOTOR

7.5 kW

#### **VOLTAGES**

220/240 V, 1Ph, 50/60 Hz

220/240 V, 3Ph, 50 Hz

380/415 V, 3Ph, 50 Hz

208/240 V, 3Ph, 60 Hz

Other voltages available on request

#### DIMENSIONS

1140 X 1000 X 1280 mm

#### (45 × 39 × 50") PACKAGING

1600 X 1200 X 1600 mm

(63 x 47 x 63")

#### **NET WEIGHT**

240 kg (529 lb)

#### **GROSS WEIGHT**

280 kg (617 lb)

#### TECHNICAL FEATURES

Diameter of the suction connection: 150 mm (6")

Options: Pneumatic bending system, scalloped blade

#### **OPTIONAL**

