

# S DUO 30

STARTER & PROFESSIONAL WORKSHOP  
BENCHTOP, INTEGRATED CUTTING & SKIVING



## KEY FEATURES

- Compact design
- Two operations in one machine
- Easy and safe to use
- Versatile, scalloped blade for high performance and efficient cutting with minimal smoke
- Dust free skive operation (drawers for dust collection)
- Electronic brake

CUTTING  
MACHINES

5

## STANDARD



Scalloped Blade



2 Dust Collectors

## TECHNICAL SPECIFICATIONS

### CAPACITY

- 2wb: 2" max.
- 4ws: 2" max.
- 6ws: 1¾" max.
- Industrial: 2" max.

### VOLTAGES

- 220/240 V, 1Ph, 50/60 Hz
- 220/240 V, 3Ph, 50 Hz
- 380/415 V, 3Ph, 50 Hz
- 208/240 V, 3Ph, 60 Hz
- Other voltages available on request

### ROTATION SPEED (CUT)

3000 rpm

### ROTATION SPEED (SKIVE)

200 rpm

### SCALLOPED BLADE DIAMETER

300 mm (11.8")

### MAX HOSE OD.

85 mm (3.34")

### MOTOR

2.2 kW

### DIMENSIONS

835 x 545 x 640 mm  
(33 x 21 x 25")

### PACKAGING

1170 x 770 x 1100 mm  
46 x 30 x 43"

### NET WEIGHT

85 kg (187 lb)

### GROSS WEIGHT

100 kg (220 lb)

### TECHNICAL FEATURES

Skiving tools for External Skiving (ESE) and for Internal Skiving (IS) to be ordered separately

## OPTIONAL



Cutting Rail



Tool Kit ESE



Tool Kit IS



Smoke extractor